



OS-M-FS



FEATURES

WARNING

Compact one piece fittings can be used only for tube cleaning application where the hose termination will be contained in the exchanger tube when under pressure. These fittings are not intended for applications where the hose termination will be exposed when under pressure.

| Part no. | Description | Minimum pack quantity | Insert tail ID mm | Thread F | Hose size | HEX-CH | HEX-CH | WP (psi) | Hoses |
|----------|--------------------|--------------------------|-------------------|------------|-----------|--------|--------|-------------|-------|
| OSA101 | 1/8 M-FS A 3/16 1P | 10 | 3.5 | 1/8-28 GAS | DN5 | 3/16 | 0 | 22000 | 2021 |
| OSJ101 | 1/8 M-FS J 3/16 1P | 10 | 3.5 | 1/8-28 GAS | DN5 | 3/16 | 0 | 22000 | 2121 |
| OSA122 | 1/4 M-FS A 1/4 1P | 10 | 4 | 1/4-19 GAS | DN6 | 1/4 | 0 | 22000 | 2022 |

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 18/05/2024

www.transferoil.com