



TRANSFER OIL

Pure Fluid Attitude

Crimping details

最近更新： 29/07/2026

126 - R8 绝缘管

Transfer Oil reserve the rights to introduce improving modifications whenever necessary.

The listed crimping data have been developed in Transfer Oil R&D laboratories and refer to tests carried out on thermoplastic hoses manufactured by Transfer Oil, and specific Transfer Oil approved ferrules and fittings.

Such values are anyway to be considered advisory and not binding for Transfer Oil because the impossibility to consider technical variability like the swaging machine used, the set of crimping dies used, the speed of the crimping process, the tolerances of each single item involved, etc.

For new applications or for hoses, ferrules and fittings not listed in this file please contact us, and we will be happy to help you in finding the best match.

Part no.	Description	Dash	Inches	DN	ID (mm)	OD (mm)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Ferrule part n°	Ferrule material	Crimping diameter (mm)	Crimping diameter (inch)	Bore collapse (mm)	Bore collapse (inch)	go/nogo gauge	dies set* (mm)
1261	3/16 R8 NON CONDUCTIVE	-3	3/16	DN5	5.0	8.9	350	5000	1400	20000	SAB811	Stainless Steel (A316L)	11.6	0.457	0.4	0.0157	N/A	10
1261	3/16 R8 NON CONDUCTIVE	-3	3/16	DN5	5.0	8.9	350	5000	1400	20000	SAB111	Carbon Steel	11.6	0.457	0.4	0.0157	N/A	10
1262	1/4 R8 NON CONDUCTIVE	-4	1/4	DN6	6.5	11.5	350	5000	1400	20000	SAB821	Stainless Steel (A316L)	14.1	0.555	0.3	0.0118	N/A	14
1262	1/4 R8 NON CONDUCTIVE	-4	1/4	DN6	6.5	11.5	350	5000	1400	20000	SAB121	Carbon Steel	14.1	0.555	0.3	0.0118	N/A	14
1263	5/16 R8 NON CONDUCTIVE	-5	5/16	DN8	8.1	13.4	300	4300	1200	17200	SAB831	Stainless Steel (A316L)	16.6	0.654	0.3	0.0118	N/A	16
1263	5/16 R8 NON CONDUCTIVE	-5	5/16	DN8	8.1	13.4	300	4300	1200	17200	SAB131	Carbon Steel	16.6	0.654	0.3	0.0118	N/A	16
1264	3/8 R8 NON CONDUCTIVE	-6	3/8	DN10	9.7	15.5	280	4000	1120	16000	SAB841	Stainless Steel (A316L)	18.2	0.717	0.5	0.0197	N/A	16
1264	3/8 R8 NON CONDUCTIVE	-6	3/8	DN10	9.7	15.5	280	4000	1120	16000	SAB141	Carbon Steel	18.2	0.717	0.5	0.0197	N/A	16
1265	1/2 R8 NON CONDUCTIVE	-8	1/2	DN12	13.0	19.9	245	3500	980	14000	SAB851	Stainless Steel (A316L)	22.6	0.890	0.8	0.0315	N/A	19
1265	1/2 R8 NON CONDUCTIVE	-8	1/2	DN12	13.0	19.9	245	3500	980	14000	SAB151	Carbon Steel	22.6	0.890	0.8	0.0315	N/A	19
1266	5/8 R8 NON CONDUCTIVE	-10	5/8	DN16	16.3	23.4	200	2900	800	11600	SAB861	Stainless Steel (A316L)	26.2	1.031	0.5	0.0197	N/A	23
1266	5/8 R8 NON CONDUCTIVE	-10	5/8	DN16	16.3	23.4	200	2900	800	11600	SAB161	Carbon Steel	26.2	1.031	0.5	0.0197	N/A	23
1267	3/4 R8 NON CONDUCTIVE	-12	3/4	DN20	19.5	27.1	165	2300	660	9200	SAB871	Stainless Steel (A316L)	29.8	1.173	0.5	0.0197	N/A	27
1267	3/4 R8 NON CONDUCTIVE	-12	3/4	DN20	19.5	27.1	165	2300	660	9200	SAB171	Carbon Steel	29.8	1.173	0.5	0.0197	N/A	27
1268	1 R8 NON CONDUCTIVE	-16	1	DN25	25.9	34.0	140	2000	560	8000	SAB881	Stainless Steel (A316L)	37.8	1.488	0.5	0.0197	N/A	36
1268	1 R8 NON CONDUCTIVE	-16	1	DN25	25.9	34.0	140	2000	560	8000	SAB181	Carbon Steel	37.8	1.488	0.5	0.0197	N/A	36

* The dies set indicated are a standard die set for FinnPower FP20 swaging machine, as used in the R&D laboratory of Transfer Oil, used to verify the swaging parameters.