



# TRANSFER OIL

Pure Fluid Attitude



## 063 - R7 ANTIABRASION TWIN

Thermoplastic hose with MSHA approved cover, for hydraulic applications from 70 to 210 bar (1000 to 3000 psi)



### FEATURES

#### Inner Tube

Polyester elastomer

#### Reinforcement

One or two braids of synthetic fiber

#### Cover

Polyurethane - black - pinpricked - laser branding

#### Applications

Construction and agricultural equipment - Agricultural brake systems - Forklift Trucks - Articulating and telescopic booms - Aerial platforms - Scissor lifts - Cranes - General hydraulics - Industrial gases

#### Features

Lighter more flexible and more compact than traditional R1 hoses - Bonded construction - Abrasion resistant - Limited change in length - Pinpricked cover

#### Description

Meets or exceeds SAE 100R7 - Medium pressure hose suitable for hydraulic applications with increased resistance to abrasion - For use with petroleum synthetic or water based hydraulic fluids in hydraulic systems - Suitable for general fluid power transmissions like earthmoving agricultural machinery and forklifts trucks - Also suitable for many industrial gases (check for compatibility) - Cover approved by MSHA (Mine Safety and Health Administration) - number IC-305.

#### Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F); limited to 70 °C (158 °F) for air and water based fluids


#### Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

#### Specifications

SAE 100R7 // EN855-R7 // ISO3949-R7

#### Standard Branding

 **TRANSFER OIL** - TO HYDRAULIC - Part No - R7 ANTIABRASION TWIN - SAE 100R7-Dash Size - Inch Size - DN Size - WP bar / psi - MSHA IC-305 - MADE IN ITALY - [www.transferoil.com](http://www.transferoil.com) - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
0630	DN4	1/8	-2	4.0	8.3	210	840	0.157	0.327	3000	12000	4:1	25	0.98	97	0.065	SAB101	SAB801
0631	DN5	3/16	-3	5.0	9.6	210	840	0.197	0.378	3000	12000	4:1	25	0.98	125	0.084	SAB111	SAB811
0632	DN6	1/4	-4	6.5	12.2	210	840	0.256	0.480	3000	12000	4:1	35	1.38	201	0.135	SAB121	SAB821
0633	DN8	5/16	-5	8.1	14.3	190	760	0.319	0.563	2700	10800	4:1	45	1.77	265	0.178	SAB131	SAB831
0634	DN10	3/8	-6	9.7	16.0	160	640	0.382	0.630	2300	9200	4:1	55	2.17	303	0.204	SAB141	SAB841
0635	DN12	1/2	-8	13.0	20.3	140	560	0.512	0.799	2000	8000	4:1	75	2.95	449	0.302	SAB151	SAB851
0636	DN16	5/8	-10	16.3	23.7	105	420	0.642	0.933	1500	6000	4:1	110	4.33	561	0.377	SAB161	SAB861
0637	DN20	3/4	-12	19.5	27.1	90	360	0.768	1.067	1300	5200	4:1	140	5.51	681	0.458	SAB171	SAB871
0638	DN25	1	-16	25.9	34.0	70	280	1.020	1.339	1000	4000	4:1	190	7.48	927	0.623	SAB181	SAB881

---

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.  
 Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.  
 Document date: 26/06/2026  
[www.transferoil.com](http://www.transferoil.com)*