TRANSFER OIL
Pure Fluid Attitude

# 157 - CPPA 3600 - PAINT SPRAY ANTISTATIC

Thermoplastic antistatic constant pressure hose for paint spray and solvent applications up to 250 bar (3600 psi)




## FEATURES

### Inner Tube

Coextruded conductive polyamide and polyamide PA6

### Reinforcement

One or two braids of synthetic fiber

### Cover

Polyurethane - blue - pinpricked - laser branding

### Applications

Airless paint spray systems - Applications requiring high chemical resistance to solvents and aggressive fluids

### Features

Coextruded inner tube - Conductive inner layer - Yarn braid design for lightweight and high flexibility - Blue pinpricked cover

### Description

Medium pressure hose with blue cover particularly designed for paint spray and solvent applications with increased resistance to abrasion and anti-pulsation effect - The inner conductive layer allow static charge dissipation without need of auxiliary systems - Due to low dissipation rate of the tube the hose is also suitable for many industrial gases - Check compatibility list for overview of resistance to chemical substances and gases - This hose is expressly intended for use in static discharge applications.

### Temperature Range

-40 °C to +100 °C (-40 °F to +212 °F) limited to +70 °C (+158 °F) for air and water based fluids

### Specification

Meets or exceeds pressure rating of SAE 100R7 // EN855 -R7 // ISO3949 -R7

Meets antistatic requirements of ISO 8031 for assemblies 100m (328 ft) or less.

### Standard Branding

TRANSFER OIL - TO INDUSTRIAL - Part No - CPPA 3600 - CONSTANT PRESSURE PAINT SPRAY ANTISTATIC - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN | Inches | Dash | ID (mm) | OD (mm) | WP (bar) | BP (bar) | ID (inch) | OD (inch) | WP (psi) | BP (psi) | SF | BR (mm) | BR (inch) | Weight (gr/m) | Weight (lb/ft) | Ferrule standard | Ferrule A316L |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1571 | DN5 | 3/16 | -3 | 5.0 | 9.6 | 250 | 1000 | 0.197 | 0.378 | 3600 | 14400 | 4:1 | 25 | 0.98 | 57 | 0.038 | SAB111 | SAB811 |
| 1572 | DN6 | 1/4 | -4 | 6.5 | 13.0 | 250 | 1000 | 0.256 | 0.512 | 3600 | 14400 | 4:1 | 35 | 1.38 | 108 | 0.073 | SAB121 | SAB821 |
| 1574 | DN10 | 3/8 | -6 | 9.7 | 18.0 | 250 | 1000 | 0.382 | 0.709 | 3600 | 14400 | 4:1 | 55 | 2.17 | 165 | 0.111 | SAC141 | SAC841 |

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.*

*Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.*
*Document date: 25/11/2026*
*www.transferoil.com*