




SOD - M-NPT VHP C

VHP NPTF 外螺纹直接头 - 700 bar



碳钢零件号	AISI 316L 不锈钢零件号	产品描述	最小包装量	软管规格	螺纹规格 F		
SOD101		1/8 M-NPT VHP C 3/16	20	DN5	3/16	27	1/8 "
SOD121	SOD821	1/4 M-NPT VHP C 3/16	20	DN5	3/16	18	1/4 "
SOD122	SOD822	1/4 M-NPT VHP C 1/4	20	DN6	1/4	18	1/4 "
SOD142	SOD842	3/8 M-NPT VHP C 1/4	20	DN6	1/4	18	3/8 "
SOD143		3/8 M-NPT VHP C 5/16	20	DN8	5/16	18	3/8 "
SOD144	SOD844	3/8 M-NPT VHP C 3/8	20	DN10	3/8	18	3/8 "
SOD155	SOD855	1/2 M-NPT VHP C 1/2	20	DN12	1/2	14	1/2 "
SOD177	SOD877	3/4 M-NPT VHP C 3/4	2	DN20	3/4	14	3/4 "
SOD188	SOD888	1 M-NPT VHP C 1	2	DN25	1	11,5	1 "

为提高产品性能和可靠性，所示尺寸和数值可在不事先通知的情况下更改。
Transfer Oil S.p.A. 对本规格表中出现的错误不承担任何责任。
文本日期: 10/06/2026
www.transferoil.com