



148 - CPLT 3600 NEO TWIN

Thermoplastic constant pressure hose with low temperature specifications (-55 °C/-67 °F) for hydraulic applications up to 250 bar (3600 psi)



FEATURES

Inner Tube

Polyester elastomer

Reinforcement

One or two braids of synthetic fiber

Cover

Special polyester - black - non pinpricked - laser branding

Applications

Forklift handling - All industrial and agricultural applications exposed to low temperatures or frequent temperature changes

Features

2 polyester braid construction from 1/4-DN6 onwards- Optimum bonding between the tube the braids and the cover - Special polyester cover resistant to low temperatures and meteorological harsh conditions - Tight bend radii without cover wrinkling

Description

Medium pressure hose suitable for petroleum or synthetic based hydraulic fluids in hydraulic systems of forklifts. Optimum bonding characteristics and special cover also make it the ideal hose for equipment operating in cold environments while maintaining a high level of flexibility. Suitable for power chains

Temperature Range

-55 °C to +100 °C (-67 °F to +212 °F): limited to +70 °C (+158 °F) for air and water based fluids

Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

Specifications

Exceeds pressure rating SAE 100R18 // ISO3949-R18

Standard Branding

TRANSFER OIL - TO HYDRAULIC - Part No - CPLT 3600 NEO TWIN - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN | Inches | Dash | ID (mm) | OD (mm) | WP (bar) | BP (bar) | ID (inch) | OD (inch) | WP (psi) | BP (psi) | SF | BR (mm) | BR (inch) | Weight (gr/m) | Weight (lb/ft) | Ferrule standard | Ferrule A316L |
|----------|------|--------|------|------------|------------|-------------|-------------|--------------|--------------|-------------|-------------|-----|------------|--------------|------------------|-------------------|---------------------|------------------|
| 1481 | DN5 | 3/16 | -3 | 5.0 | 9.6 | 250 | 1000 | 0.197 | 0.378 | 3600 | 14400 | 4:1 | 25 | 0.98 | 120 | 0.081 | SABIII | SAB811 |
| 1482 | DN6 | 1/4 | -4 | 6.5 | 13.0 | 250 | 1000 | 0.256 | 0.512 | 3600 | 14400 | 4:1 | 35 | 1.38 | 220 | 0.148 | SAB121 | SAB821 |
| 1483 | DN8 | 5/16 | -5 | 8.1 | 15.2 | 250 | 1000 | 0.319 | 0.598 | 3600 | 14400 | 4:1 | 45 | 1.77 | 280 | 0.188 | SAB131 | SAB831 |
| 1484 | DN10 | 3/8 | -6 | 9.7 | 18.0 | 250 | 1000 | 0.382 | 0.709 | 3600 | 14400 | 4:1 | 45 | 1.77 | 410 | 0.276 | SAC141 | SAC841 |

www.transferoil.com